



## Remote Road State Sensor DSC211

DSC211 is the latest member of the DSC family with more sensitive measurement of the amount of water, ice, or snow on the road. Also, the improved autocalibration provides long-term stability by better adapting to the wear and tear of the road surface.



### Features

- Measures the amount of water, ice, or snow on the road or runway surface
- Provides road state and grip based on the amount of water, ice, or snow
- Accurate and reliable measurements even with intense traffic
- Easy and low-cost installation and maintenance since there is no need for traffic control
- Can operate standalone, as a standalone solution with DST111, or as a sensor in a road weather station

Compared to its predecessor DSC111, DSC211 offers the following:

- Improved accuracy and sensitivity of the measurement of the amount of water, ice, or snow
- Enhanced autocalibration

### No traffic disruption for installation or maintenance

The remote sensor DSC211 eliminates the traffic disruption caused by installation and maintenance. Remote installation means that there is no need to cut the road surface or to close the road. The sensor can be installed in a remote location to a pole adjacent to the road, or as an addition to Vaisala Road Weather Station RWS200.

### Improved sensitivity for earlier warnings

The spectroscopic measuring principle enables accurate measurement of the amount of water, ice, or snow on the road surface. In addition, DSC211 provides road state and grip, which is a calculated estimate of friction.

DSC211 has a clearly improved sensitivity and accuracy compared to DSC111. It provides an accurate measurement of the presence of ice crystals well before they make the road slippery. The earlier warnings enable the winter maintenance engineer to react before the road becomes hazardous for drivers.

### Frost detection and enhanced autocalibration

DSC211 requires air temperature, relative humidity, and road temperature observations from another sensor or system for frost detection and enhanced autocalibration. DSC211 can be connected to Vaisala Remote Road Temperature Sensor DST111, which provides these observations to DSC211.

For the most accurate and reliable observations, Vaisala recommends using DSC211 as a sensor in the Vaisala RWS200 or RWCC road weather station. RWS200 and RWCC automatically reports observation values from the most reliable sensor in the system, for example, air temperature and relative humidity from Vaisala HUMICAP® Humidity and Temperature Probe HMP155.

With certain limitations, DSC211 can be connected to Vaisala legacy road weather stations LX-RPU and ROSA.

### Optional visibility measurement

The optional visibility measurement offers a useful, compact, and extremely cost-effective way to measure the meteorological optical range (MOR). The visibility measurement extends the capabilities of DSC211 to detect low visibility conditions – without any external hardware.

### Upgrade from DSC111 to DSC211

Because DSC111 and DSC211 share the same hardware, you can usually upgrade your DSC111 to DSC211 just by purchasing the software. To make sure that your system configuration is compatible with DSC211, please contact Vaisala.

# DSC211 technical data

## Measurement performance

Measuring distance with visibility observation disabled	2 ... 15 m (6 ft 7 in ... 49 ft 3 in)
Measuring distance with visibility observation enabled	8 ... 15 m (26 ft 3 in ... 49 ft 3 in)
Installation angle from the horizontal line	30 ... 80° (35 ... 65° recommended)
Diameter of measuring area at 10 m (33 ft)	20 cm (7.87 in)
<b>Surface layer thickness</b>	
Water	0.00 ... 2 mm (0.00 ... 0.06 in)
Ice	0.00 ... 2 mm (0.00 ... 0.06 in)
Snow	0.00 ... 10 mm (0.00 ... 0.40 in)
Snow (water equivalent)	0.00 ... 1 mm (0.00 ... 0.04 in)
Accuracy, water and ice	±0.1 mm in the range of 0 ... 1 mm (0 ... 0.04 in)
<b>Grip</b>	
Reported level of grip	0.09 ... 0.82
<b>Reported surface states</b>	
Vaisala classes	Dry, moist, wet, frosty <sup>1)</sup> , snowy, icy, slushy
EN 15518-3 classes	Dry, moist, wet, streaming water, slippery
<b>Visibility (optional)</b>	
Observation range (meteorological optical range, MOR)	10 ... 2000 m (33 ... 6572 ft)
Resolution	1 m (3 ft 3 in)
Accuracy (fog and snowfall)	±20 % (average)
Response time	60 s

<sup>1)</sup> Frost is only reported when dew point and road temperature information is available.

## Inputs and outputs

Connectors	3 × M12 (5 pins) RS-485 and power out for DST111, female RS-485 and power in, male RS-232, male
Communication interface	RS-485 isolated, RS-232
Sensor support	DST111
Input voltage	9 ... 30 V DC
Maximum input current	0.25 A at 24 V
Date and time	Real-time clock with battery backup
Settling time before dry calibration	5 min
<b>Typical power consumption</b>	
At above -10 °C (+14 °F)	1.13 W at 24 V
At below -10 °C (+14 °F)	1.90 W at 24 V
With lens heating on	5.25 W at 24 V

## Operating environment

Operating temperature	-40 ... +60 °C (-40 ... +140 °F)
Storage temperature	-55 ... +60 °C (-67 ... +140 °F)
Operating humidity	0 ... 100 %RH
IP rating	IP65

## Compliance

EU directives	Low Voltage Directive (2014/35/EU) EMC Directive (2014/30/EU) RoHS Directive (2011/65/EU) amended by 2015/863
EMC immunity	EN 61326-1, industrial environment FCC part 15, class B ICES-3 (B)
EMC emissions	CISPR 32 / EN 55032, Class B
Eye safety	IEC 60825-1:2014 Class 1 laser product
Vibration	IEC 60068-2-6

## Mechanical specifications

Dimensions (H × W × D)	210 × 133 × 448 mm (8.27 × 5.24 × 17.64 in)
Weight	Sensor: 2.69 kg (5.93 lb) Mounting bracket: 0.71 kg (1.57 lb)
Mounting	Fits on a sensor support arm with cross-section of 40 × 40 mm (1.57 × 1.57 in)
Cables	3 ... 150 m (9 ft 10 in ... 492 ft) One end without connector 0.6 m (1 ft 12 in) extension cable to DST111
<b>Materials</b>	
Cover	ABS plastic
Transmitter body	POM plastic
Bolts, screws, and washers Fixture plate of the cover	Stainless steel
Lenses and windows	Glass
Other parts	Aluminum



Vaisala Remote Road Temperature Sensor DST111 presented with Vaisala Remote Road State Sensor DSC211

**VAISALA**

www.vaisala.com

Published by Vaisala | B211701EN-A © Vaisala 2021

All rights reserved. Any logos and/or product names are trademarks of Vaisala or its individual partners. Any reproduction, transfer, distribution or storage of information contained in this document is strictly prohibited. All specifications – technical included – are subject to change without notice.